

Cobra Radial G/T



The Cobra Radial G/T is Cooper's all-season cosmetic performance tyre that is targeted at buyers who prefer raised white-letter styling in an all-season tyre.

The Cobra Radial G/T is especially popular with drivers of older domestic "muscle cars" who still want to retain the characteristic "look" of their vehicle.

Please note these tyres are ordered on request.
Write to info@coopertyres.co.za

PERFORMANCE TREAD

Increased tyre-to-road contact which leads to improvements in treadwear and handling.

EVEN WEARING DESIGN

The notches, solid centre rib, along with a refined tread element shape, helps provide even treadwear. Shoulder-slotting is also designed for resistance to irregular wear while providing solid, all-season performance.

SIDEWALL AND SIZE OPTIONS

Available in a full selection of popular sizes, the Cobra G/T offers a unique, stylised, raised white letter sidewall to enhance vehicle appearance. The reverse side offers a serrated, black letter look for a more subtle effect. Some sizes are available in black lettering, only featuring a reversible option: stylised sidewall on one side and a traditional, smooth sidewall with standard lettering on the reverse.

POLY / STEEL CONSTRUCTION

Low stretch polyester plies along with strong steel cord belts provide a tough tyre body for excellent durability.

Cobra Radial G/T

Product Code	Tyre Size	RF/XL	Index	Sdwl.	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Pass Max Load (kg)	Overall Diam. (mm)
1139633	215/70R14		96T	RWL	6.5	5.5	7.0	705	654
1139634	225/70R14		98T	RWL	6.5	6.0	7.5	760	667
39602	295/50R15		105S	RWL	9.5	8.0	10.0	935	681
1139612	235/60R15		98T	RWL	7.0	6.5	8.5	745	663
1139613	245/60R15		100T	RWL	7.0	7.0	8.5	795	674
1139614	255/60R15		102T	RWL	7.5	7.0	9.0	855	686
39616	215/65R15		95T	RWL	6.5	6.0	7.5	685	660



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
Contact info@coopertyres.co.za for current information.

Zeon CS SPORT

The Cooper Zeon CS Sport is the latest addition to the ultra high performance range.

Packed with new design features, the CS Sport is orientated towards the driving enthusiast, delivering supreme performance while maximising the driving experience.

HIGH DISPERSION SILICA TREAD

Provides improved wet performance as well as excellent traction in dry conditions.

0° SPIRAL RESTRICTOR

Improved high speed performance.

2 PLY RAYON CASING

Tuned construction for exceptionally crisp, predictable handling.

FLIPPER REINFORCEMENT

Improved steering response and lateral stability.

TRI-ARC MOULD PROFILE

Developed for improved contact pressure distribution handling and balanced treadwear.

DESIGNED AND DEVELOPED WITH THE DRIVING ENTHUSIAST IN MIND

A select range of 18" and 19" sizes W and Y speed ratings.

Zeon CS Sport

Product Code	Tyre Size	RF/XL	Index	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Pass Max Load (kg)	Overall Diam. (mm)
5170013	235/40R18		91Y	8.5	8.0	9.5	615	645
5170092	245/40R18	XL	97Y	8.5	8.0	9.5	730	653
5170190	245/45R18	XL	100W	8.0	7.5	9.0	800	677
5170097	255/35R18	XL	94Y	9.0	8.5	10.0	670	635
5170098	235/35R19	XL	91Y	8.5	8.0	9.5	615	647
5170291	245/40R19	XL	98Y	8.5	8.0	9.5	750	679
5170099	255/35R19	XL	96Y	9.0	8.5	10.0	710	661



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
Contact info@coopertyres.co.za for current information.

Zeon CS8



The new Cooper Zeon CS8 high performance passenger tyre brings unprecedented “A” grade wet grip, handling and fuel efficiency. This tyre provides wet performance as well as excellent traction in dry conditions with its high dispersion silica tread. Noise damping structures reduce airborne noise generated by the tyre/road interaction. Wear Square™ visual indicator allows a quick check on approximate tread life remaining on the tyre and indicates any potential wheel alignment issues with the vehicle.

NOISE DAMPING STRUCTURES

Reduces airborne noise generated by the tyre/road interaction.

HIGH DISPERSION SILICA TREAD

Provides improved wet performance as well as excellent traction in dry conditions.

WEAR SQUARE™ VISUAL INDICATOR

The Wear Square visual indicator allows you and your customer to quickly see the approximate tread life remaining on the tyres. As the tyre wears, the shape of the Wear Square will also change. The five stages begin with a square at new and end with an exclamation mark when the tread reaches 1.59mm, indicating it is time to replace the tyres. The Wear Square is located on the inside and outside half of the tyre. Upon inspection, if the inner and outer Wear Squares are at different stages, this indicates uneven tyre wear and a possible wheel alignment issue with the vehicle.

FUNCTIONAL RIM FLANGE PROTECTORS

In all sizes help protect against kerb damage.

3D MICRO-GAUGE™

The tread pattern features 3D sipes with interlocking three dimensional points. These help the tyre warm up and provide enhanced wet grip.

ASYMMETRICAL PROFILE

It features sequenced tread blocks to reduce generated noise, whilst dimples in the tread grooves mean a quieter ride. Available in 16” to 18” rim diameters with V, W and Y speed ratings.

Zeon CS8

Product Code	Tyre Size	RF/XL	Index	EU Rating	Sdwl.	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Overall Diam. (mm)
S350111	205/55R16		91V	C A69))	BSW	6.5	5.5	7.5	632
5350017	225/45R17		91W	E A69))	BSW	7.5	7.0	8.5	634
5350195	245/45R17	XL	99Y	C A70))	BSW	8.0	7.5	9.0	652
5350190	225/40R18	XL	92W	C A70))	BSW	8.0	7.5	9.0	637



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
Contact info@coopertyres.co.za for current information.